

LA-UR-21-21636

Approved for public release; distribution is unlimited.

Title: Hemispherical Head RFQ Vendor Pre-proposal Meeting

Author(s): Bingham, Kelly L.
Guffee, Ray M.
Royer, Brandy Cox
Smouse, Thomas Dustin

Intended for: Presentation to be released to fabrication vendors that gives overview of LANL's vessel program and needs

Issued: 2021-02-19

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.



Hemispherical Head RFQ Vendor Pre-proposal Meeting

Ray Guffee, Kelly Bingham, Brandy Royer, Tom Smouse

February 18, 2021



2/19/2021



Managed by Triad National Security, LLC., for the U.S. Department of Energy's NNSA.


Mission Need

- LANL utilizes thick-walled, spherical vessels for numerous basic science, materials, and system performance experiments
- These pressure retaining vessels are designed and fabricated to meet the intent of ASME B&PV Section VIII, Division 3 and Code Case 2564
- LANL has successfully contracted past production of component parts (nozzle and cover forgings, plate production and head forming) and overall vessel construction (welding, inspection, hydrostatic testing) utilizing HSLA-100 steel
- As current vessel inventories approach design lifetimes, we are once again embarking upon a series of fabrication contracts to produce replacement components and vessel assemblies to ensure continued experiment cadence at LANL
- We anticipate releasing additional future vessel production contracts as experimental demands at LANL continue to increase



Vessels Utilized at LANL


6' dia. – 5 port




3' dia. – 5 port



LANL Vessel Configurations



6' x 2.5" Nom. Wall 5-Port Vessel



3' x 1.1" Nom. Wall 5-Port Vessel



Vessel Component Parts



Hemispherical Heads
(6' x 2.5" Nom. and 3' x 1.1" Nom.)



Nozzle Ring Forgings
(Four Sizes Utilized)



Cover Disk Forgings
(Two Sizes Utilized)

Current Hemispherical Head Needs

Size	Quantity	Estimated Weight (lbs)
3' dia x 1.1" Nom Wall	1 FA + 18 Production	17,100
6' dia x 2.5" Nom Wall	1 FA + 24 Production	170,000



- HSLA-100 Material
 - Material of choice because of strength & toughness
 - Repairable with no post-weld Heat Treatment




Contract Overview and Structure

- At least two separate fabrication contracts will be placed, each with 2 phases
 - At least one 6' Hemispherical Head contract
 - Phase 1 – First Article fabrication and acceptance of single representative head
 - Phase 2 – Production and acceptance of a maximum of 24 heads (final contract number contingent on technical evaluation criteria and number of Phase 2 contracts awarded)
 - At least one 3' Hemispherical Head contract
 - Phase 1 – First Article fabrication and acceptance of single representative head
 - Phase 2 – Production and acceptance of a maximum of 18 heads (final contract number contingent on technical evaluation criteria and number of Phase 2 contracts awarded)
 - Vendor must successfully meet all First Article technical performance criteria to be eligible/qualified for Phase 2 contract awards
 - Successful 6' Hemispherical Head First Article = Qualification for production of 6' and 3' heads
 - Successful 3' Hemispherical Head First Article = Qualification for production of 3' heads ONLY
 - Successful First Article does not guarantee award of Phase 2 contract
 - Award will be based on proposed production schedule, cost, and First Article technical performance



Qualification for Production Contract

- First Article
 - RFQ to develop your process to meet our requirements
 - Acceptable First Article technical performance
- Approved Vendor Quality Program
 - Verified during First Article phase
 - Must be established/approved prior to production award
- Award production to meet schedules
 - Production heads follow the process developed during First Article



Summary of Technical Requirements

Specified Characteristics	Requirements	Verified by
First Article	To establish means & methods of production	See items below as well as LANL Specification ENG-TS-J2-1535
Material Chemistry	Tech Pub T9704 HSLA-100 Comp 3	Chemistry & Microstructure Analysis, CMTR's
Mechanical Properties	Strength, Hardness, Ductility, Toughness	Tensile, Brinell Hardness, Charpy Impact, Charpy Transition Curves Dynamic Tear Test, & CMTR's
Soundness	Lack of voids & process defects	Wet Magnetic Particle & Ultrasonic Testing
Geometry	Fit & form must meet LANL drawing requirements	Inspection & Test Reports
Process Control	QA Program, Submittals, Travelers, Procedures, Instructions and Qualification/Certifications	Vendor QA Program Qualification, Surveillance, Inspection & Test Reports



Timeline

- Contract Introduction Meeting Feb. 18th 8:30 AM MST
- Notification of Intent to Bid due Feb. 25th 2021
- Proposals due March 5, 2021
- Intent to award by end of March



Questions and Contacts

- Contract Questions:

- Letitia Espinosa
- leme@lanl.gov
- [505 695 6209](tel:5056956209) Cell
- 505 606 1606 Work

- Technical Questions

- Ray Guffee
- guffee@lanl.gov
- 505 667 1374 Work

- QA Questions:

- Kelly Bingham
- kellyb@lanl.gov
- [505 620-9628](tel:5056209628) Cell



Backup Slides



Current Vessel & Component Needs

Current 6' Vessel Component Needs							
Vessels Needed					12	By	Mar. - 22
Description	Qty/vessel	Part Size	lbs/ piece	lbs / vessel	Qty PO	Weight PO	Tons PO
HSLA-100 Hemi-Heads	2	2.625" x 72" id.	6,800	13,600	25	170,000	85
HSLA-100 Nozzle	5	37.7" od x 23.2" id x 6.9"	1,400	7,000	60	84,000	42
HSLA-100 Cover Disks	5	34.7" od x 6.5"	1,800	9,000	70	126,000	63
Weld Metal lbs	916	Double U Joint Weld Filler	916	916	10,997	10,997	5.5
Total weight/ Vessel				30,516	Weight/ PO	390,997	195.50
Current 3' Vessel & Component Needs							
Vessels Needed					9	By	Dec. -22
Description	Qty/Vessel	Part Size	lbs/ piece	lbs / vessel	Qty PO	Weight PO	Tons PO
HSLA-100 Hemi-Heads	2	1.25" x 36" dia.	900	1,800	19	17,100	8.55
HSLA-100 Top Nozzle	1	25" od x 15.5" id x 6.4"	600	600	10	6,000	3.00
HSLA-100 Top Cover	1	22" od x 6"	540	540	9	4,860	2.43
HSLA-100 Enter Nozzle	2	17.1" od x 5.2" id x 3.8	300	600	18	5,400	2.70
HSLA-100 Exit Nozzle	2	16.5" od x 9.48" id x 3.30"	280	560	18	5,040	2.52
HSLA-100 Base Ring	1	11" od x 5.4" id x 4"	126	126	9	1,134	0.57
Weld Metal lbs	121	Double U Joint Weld Filler	121	121	1,089	1,089	0.54
Weight/Vessel				2,547	Weight/ PO	23,523	11.76



Future Vessel & Components Needs

Future 6' Vessel Needs							
Additional 6' Vessels Needed					6	By	Mar. - 25
Vessel Components							
Description	Qty/vessel	Part Size	lbs/ piece	bs / vesse	Qty	Weight	Tons
HSLA-100 Hemi-Heads	2	2.625" x 72" id.	6,800	13,600	13	88,400	44.2
HSLA-100 Nozzle	5	37.7" od x 23.2" id x 6.9"	1,400	7,000	32	44,800	22.4
HSLA-100 Cover Disks	5	34.7" od x 6.5"	1,800	9,000	32	57,600	28.8
Weld Metal lbs	916	Double U Joint Weld Filler		916	12	10,997	0.0
Total weight/ Vessel				30,516	Weight	201,797	95.41
Future 3' Vessel Needs							
Additional 3' Vessels					9	By	Dec. -25
Vessel Components Needed							
Description	Qty/Vessel	Part Size	lbs/ piece	bs / vesse	Qty	Weight	Tons
HSLA-100 Hemi-Heads	2	1.25" x 36" dia.	900	1,800	19	17,100	8.55
HSLA-100 Top Nozzle	1	25" od x 15.5" id x 6.4"	600	600	10	6,000	3.00
HSLA-100 Top Cover	1	22" od x 6"	540	540	9	4,860	2.43
HSLA-100 Enter Nozzle	2	17.1" od x 5.2" id x 3.8	300	600	18	5,400	2.70
HSLA-100 Exit Nozzle	2	16.5" od x 9.48" id x 3.30"	280	560	18	5,040	2.52
HSLA-100 Base Ring	1	11" od x 5.4" id x 4"	40	40	9	360	0.18
Weld Metal lbs	121	Double U Joint Weld Filler		121	1,089	1,089	0.54
Weight/Vessel				2,461	Weight	22,749	11.37

